










Jib		Max. Load		m x t									
m	rope	t	m	18	20	25	30	35	40	45	50	55	60
60		12.00	32.43	12.00	12.00	12.00	12.00	10.89	9.46	8.42	7.45	6.73	6.20
50		12.00	39.71	12.00	12.00	12.00	12.00	12.00	11.88	10.40	9.50		
		24.00	20.46	24.00	24.00	19.40	15.48	13.28	11.42	10.11	9.20		
40		12.00	40.00	12.00	12.00	12.00	12.00	12.00	12.00				
		24.00	22.57	24.00	24.00	21.40	17.34	14.81	13.20				
30		12.00	30.00	12.00	12.00	12.00	12.00						
		24.00	22.81	24.00	24.00	21.53	18.30						

Hoisting 2×75 kW Fi				Luffing 75 kW Fi		Slewing 2x145Nm Fi	Traveling 4x7.5kw	
P _{max}		12.0 - 24.0 [t]			15°~85° t=1.90		0,67 rpm	25 m/min
	Load [to]	3.5	7.9	12.0	Power requirement (upper part) 280kVA		Fi → Frequency inverter	
	V [m/min]	124	93	62				
	Load [to]	8.7	15.5	24.0	Power requirement (upper part) 280kVA		Fi → Frequency inverter	
	V [m/min]	62	46.5	31				